

52 - 61 L/day

**This high capacity dehumidifier is for professional and commercial applications**, helping to combat excess moisture in swimming pools, bathing and leisure areas, food preparation areas, stores, archives, museums, libraries and many more locations.

- Installed dehumidifier
- Electronic defrost control
- Rotary compressor
- Mains plug fitted
- Wall mounting bracket
- Free standing on 4 feet
- Electronic humidistat
- Washable air filter
- 2 speed fan
- Adjustable air louvers
- Power on indicator
- Drying indicator
- Digital humidity readout
- Electronic touch controls

#### TECHNICAL DATA

TYPE: Wall Fixed Industrial Dehumidifier	D850E/R410A	D950E/R410A	
Mains	230 V / 50 Hz		
Power consumption	W	915	1360
Current (operation)	A	4,15	6,5
Current (at start)	A	20	22
Water extraction at	L/24h		
30 °C, 70 % RH		52	61
30 °C, 80 % RH		60	76
32 °C, 90 % RH		63	81
Refrigerating agent R410A*	g	540	700
Airflow (at high fan speed)	m <sup>3</sup> /h	650	830
Operating temperature	°C	7 - 35	
Dimensions w x d x h	mm	660 x 345 x 750	
Weight (net)	kg	37	39

Meets EEC directive 73/23/CE (LVD).

Specifications may change without prior notice.



**The solution against humidity.**

**ECOR<sup>PRO</sup>**